## MATERIAL SAFETY DATA SHEET

Product:	SBF-12, SBF-12BK, SBF-12CQ, SBF-17 SBF-17CQ, SBF-17BK, SBF-18, SBF-18BK	Trade Name:	Silicone Brake Fluid
Manufacturer: Street Address:	AGS Company 2651 Hoyt St	Common Name:	DOT 5 Brake Fluid
City/State/Zip Phone: Phone: FAX: Transportation Emerge Phone:	Muskegon Hts., MI 49444 800-253-0403 231-733-2101 231-733-1784	Original Issue Date: Revision N⊨ 7	10/8/1993 Date 2/1/2007
	SECTION 2 - COMPOSITION/ INFOR	RMATION ON INGREDIE	NTS
ITEM 1 Tributyl Pho	osphate	CAS NUMBER 126-73-8	WT/WT % 1-5
ITEM TLV-TWA 1 2	EXPOSURE LIMITS ACGIH TLV-STEL PEL-TW mg/m <sup>3</sup> (See Section 16 for al SECTION 3 - HAZARDS	5 mg/m <sup>3</sup> 30 bbreviation legend)	ING ppm IDLH
EYE CONTACT:	May be irritating and can cause pain, tearing,		
SKIN CONTACT:	Prolonged contact may result in irritation.	ind owning.	
NHALATION:	May cause irritation to the muscous membrar	nes.	
INGESTION:	This material may be harmful if swallowed.		
CHRONIC HAZARDS:	Prolong inhalation of vapors can cause gener	al poisoning and paralysis	5.
Primary Route(s) of Ent	r Skin and eye contact or ingestion and inhalati	on.	
	SECTION 4 - FIRST A	ID MEASURES	
EYE CONTACT: Immed	diately flush eyes with plenty of water. Get me	edical attention, if irritation	n persists
	ediately flush with plenty of water. Remove clo hing separately before reuse.	othing. Get medical atter	tion
INHALATION: Remove give oxygen. Get immed	to fresh air. If not breathing, give artificial res iate medical attention.	spiration. If breathing is o	difficult,
	cal attention immediately. If swallowed, DO NO r poison control center immediately. Never giv	-	-
	SECTION 5 - FIRE FIGHT	TING MEASURES	
FLASH POINT:		EXPLOSIVE LIMIT: EXPLOSIVE LIMIT:	N.D. % N.D. %
AUTOGNITION TEMPER	ATURE: N.D.		
EXTINGUISHING MEDIA	CO <sub>2</sub> , Dry Chemical, Foam		
UNUSUAL FIRE AND E	XPLOSION HAZARDS: Product can produce	dense smoke from oils bu	rning.

	MATERIAL SAFETY DATA SHEET			
protective gear.				
	SECTION 6 - ACCIDENTAL RELEASE MEASURES			
RECOVERY PROCEDURES:	Absorb with an inert material and place in a chemical waste container.			
	SECTION 7 - HANDLING AND STORAGE			
HANDLING: Wash thoroughly after h	andling			
STORAGE: Store in cool dry enviro	nment.			
SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION				
SEC	CTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION			
ENGINEERING CONTROLS:	CTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION General exhaust to maintain concentration below the PEL.			
ENGINEERING CONTROLS: RESPIRATORY PROTECTION:				
ENGINEERING CONTROLS: RESPIRATORY PROTECTION: however, if high vapor concentration	General exhaust to maintain concentration below the PEL. For most conditions, no respiratory protection should be needed,			
ENGINEERING CONTROLS: RESPIRATORY PROTECTION: however, if high vapor concentration SKIN PROTECTION: Where con	General exhaust to maintain concentration below the PEL. For most conditions, no respiratory protection should be needed, should develop, use a NIOSH approved organic vapor respirator.			

HYGIENIC PRACTICES: Wash hands before eating. Remove contaminated clothing and wash before reuse. Use only in a well ventilated area. Follow all MSDS / label precautions even after container is emptied because they may retain product residues. Avoid prolonged or repeated contact with eyes, skin, and clothing.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE ODOR APPEARANCE SOLUBILITY IN H <sub>2</sub> O	N.A. Odorless Purple Color Insoluble	VAPOR DENSITY: ODOR THRESHOLD EVAPORATION RATE	Is heavier than air N.D. Is slower than Butyl Acetate			
POUR POINT	-67°F	SPECIFIC GRAVITY	0.958 at 25°C			
VAPOR PRESSURE	< 0.1 mmHg @ 20°C	pH @ 0.0%	N.A.			
PHYSICAL STATE	Liquid	VISCOSITY:	42-43 cs at 25°C			
COEFFICIENT OF WATER / OIL DISTRIBUTION Negligible						

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID Sources of ignition.

INCOMPATIBILITY: Strong acid or alkali, oxidizers and amines.

HAZARDOUS DECOMPOSITION PRODUCTS Oxides of carbon, nitrogen, phosphorus and silica.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions

STABILITY: This product is stable under normal storage conditions.

## SECTION 11 - TOXICOLOGICAL PROPERTIES

PRODUCT	LD-50	1863 mg/kg	PRODUCT	LC-50	123 ppm			
COMPONENT TOXICOLOGICAL INFORMATION:								
Dimethylpoly Tributyl Phos					mg/kg/rat mg/kg/adult hen	LC50 N.E. 123 ppm/6 hr/rat		
SECTION 12 - ECOLOGICAL INFORMATION								

	MATERIAL SAF	ETY DATA SHE	ET
ECOLOGICAL INFORMATION:	LC50 Carp >10,000 mg/l/7:	2 hr /Conditions o	f bioassay not specified
	SECTION 13 - DISPO	SAL CONSIDER	ATIONS
DISPOSAL METHOD: Dispose o	f in accordance with federal, s	tate and local reg	ulations.
	SECTION 14 - TRANSP	ORTATION INFO	RMATION
DOT PROPER SHIPPING NAME	Not regulated		
DOT TECHNICAL NAME			
DOT HAZARD CLASS	НА	ZARD SUBCLAS	S:
DOT UN / NA NUMBER:	PACKING GRO	UP: N/	RESP. GUIDE PAGE
	SECTION 15 - REGU		
U.S FEDERAL REGULATIONS:	AS FOLLOWS -		
			222
OSHA: Hazardous by definition of H	Hazard Communication Standa	ard (29 cfr 1910.1	200)
CERCLA - SARA HAZARD CATEG This product has been reviewed acc 311 and 312 of the Superfund Amer considered, under applicable definiti	ording to the EPA 'Hazard Cat adment and Reauthorization A	ct of 1986 (SARA	
Acute health hazard			
SARA SECTION 313 This product contains the following s of the Superfund Amendments and		•	
		S NUMBER	WT /WT % IS LESS THAN %
No SARA Section 313 components TOXIC SUBSTANCE CONTROL AC This product contains the following of if exported from the United States:	T:	o the reporting rec	
CHEMICAL NAME	CA	S NUMBER	
Dimethylpolysiloxane Tributyl Phosphate		48-62-9 26-73-8	
U.S. STATE REGULATIONS:	AS FOLLOWS -		
NEW JERSEY RIGHT-TO-KNOW: The following materials are non-haz		five components	in this product:
CHEMICAL NAME Dimethylpolysiloxane		S NUMBER 148-62-9	
PENNSYLVANIA RIGHT-TO-Know The following non-hazardous ingredi	ents are present in the product	t at greater than 3	%:
CHEMICAL NAME Dimethylpolysiloxane		S NUMBER 148-62-9	
CALIFORNIA PROPOSITION 65: WARNING: The chemical(s) noted to causes cancer, birth defects or o		oduct, are know to	o the state of California
CHEMICAL NAME No Proposition 65 chemicals exist ir		S NUMBER	

## MATERIAL SAFETY DATA SHEET

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No inform		ormation availabl	e.					
		SECTION 16	- OTHER I	NFORMATION				
HMIS RATINGS:	Health 2	Flammability	y 1	Phys. Haz.	0	PPE	A	
NFPA	Health 2	Flammability	y 1	Reactivity	0			
VOLATILE ORGANIC	C COMPOUNDS (VOCs)	. 0.00	lbs / gal	0 ç	grams /	liter		
LEGEND: N.A. N.D.	Not Applicable Not Determined	N.E.	Not Estal	olished				