MATERIAL SAFETY DATA SHEET

Warren Unilube, Inc.

Address: 915 E. Jefferson Ave.

West Memphis, AR 72301

Phone: (800) 428-9284

Chemtrec Number: Domestic: (800) 424-9300 International: (703) 527-3887

PRODUCT IDENTIFICATION

Trade Name: CARQUEST DOT 3 Brake Fluid Date Revised: February 5, 2010

Chemical Name: N.A.

DOT Hazard Class: Not Applicable

NFPA Codes: Health=1, Flammability=1, Reactivity=0

COMPOSITION

Occupational Exposure Limits*

<u>Product</u>	CAS Number	<u>Wt%</u>	
CARQUEST DOT 3 Brake Fluid***	Mixture	100	
Ingredient(s):			
Triethylene Glycol Monomethyl Ether	112-35-6	5 – 50	_
Triethylene Glycol Monoethyl Ether	112-50-5	5 - 50	
Triethylene Glycol Monobutyl Ether	143-22-6	5 - 50	
Tetraethylene Glycol Monobutyl Ether	1559-34-8	5 - 20	
Polyethylene Glycol	25322-68-3	5 - 20	
Diethylene Glycol Monobutyl Ether	112-34-5	5 - 20	
Diethylene Glycol	111-46-6	5 – 15	
Diethylene Glycol Monomethyl Ether	111-77-3	<5	
Diethylene Glycol Monoethyl Ether	111-90-0	<5	
Polyalkylene Glycol Monobutyl Ether	9004-77-7	5 - 20	
Polyalkylene Glycol Monomethyl Ether	23783-42-8	5 - 20	
Polyalkylene Glycols	9038-95-3	5 - 20	
Trade Secret Inhibitor Package	Trade Secret	<3	

^{* = 8-}Hr. TWA unless otherwise specified.

^{** =} As mineral oil Mist

^{*** =} All ingredients in this product are listed in the T.S.C.A. Inventory.

N.A. = Not Available

N.A.-P = Information is claimed proprietary by supplier.

STEL = Short Term Exposure Limit; 15 minutes.

PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point 760 mmHg: 401°F Melting Point: N.A.

Vapor Pressure mmHg @ 20C <0.1 Vapor Density (air=1): N.A.

Solubility in H₂O %: Soluble pH: N.A.

Specific Gravity (H₂O): 1.02-1.04 Evaporation Rate (ethyl ether =1): N.A.

% Volatile by Volume: N.A. Odor: Mild ether odor

Viscosity (method, temp): N.A. Appearance: Colorless to yellow

N.A. = Not Available

FIRE AND EXPLOSION DATA

Flash Point: >200F

Flammable Limits in Air % by Vol. Lower: N.A. Upper: N.A.

Autoignition Temperature: N.A.

Extinguishing Media: Dry chemical, foam, carbon dioxide.

Special Fire Fighting Procedure: Water spray may be used to keep fire-exposed containers cool, preventing pressure build-

up and explosion. Firefighters should wear self-contained breathing apparatus.

Unusual Fire or Explosion Hazard: May ignite when sufficient heat is applied.

REACTIVITY DATA

Stability: Stable

Hazardous Polymerization: Will not occur.

Conditions to Avoid/Incompatibility: Strong oxidizing agents, heat, spark, flame and build-up of static electricity.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, water and/or oxygenated hydrocarbons.

HEALTH HAZARD DATA

This product has not been tested as a whole to determine its specific health hazards. The information provided in this section is based on health hazard information on the product components.

Carcinogenicity: NTP: No IARC Monographs: No OSHA Regulated: No

Occupational Exposure Limits: See COMPOSITION section.

Effects of Overexposure:

Acute:

Eyes: May cause severe eye irritation and chemical burns.

Skin: Slightly irritating to the skin. Harmful amounts may be absorbed through the skin

with extensive and prolonged contact.

Inhalation: Exposure to vapors or mist may result in irritation of the respiratory tract,

headache, drowsiness and dizziness. High concentrations of ethylene glycol ethers may be

lethal.

Ingestion: May cause irritation of the mouth, throat, and the respiratory tract, abdominal

discomfort, dizziness, lumbar pain, CNS depression, kidney and liver damage.

Chronic: Prolonged or repeated skin contact may result in toxic amounts being absorbed through the skin.

Additional Medical and Toxicological Information:

Persons with preexisting respiratory, liver, kidney, eye or skin diseases may be adversely affected by this product. Ethylene glycol and ethylene glycol ethers have produced dose-related teratogenic effects and maternal toxicity in laboratory animals. Exposure to vapors of ethylene glycol ethers have caused testicular atrophy in laboratory animals.

EMERGENCY FIRST AID PROCEDURES

Eye Contact: Flush thoroughly with large amounts of water for at least 15 minutes, including under

the eyelids. Contact a physician immediately, preferably an Ophthalmologist. Speed

and thoroughness in rinsing eyes are important to avoid permanent injury.

Skin Contact: Remove contaminated clothing. Wash affected areas with soap and water. If irritation

occurs, get medical help. Discard contaminated shoes.

Inhalation: Remove to fresh air. Apply artificial respiration if not breathing. Get medical attention.

Ingestion: Do not induce vomiting. Get immediate medical attention.

SPECIAL PROTECTION INFORMATION

Eye Protection: Remove contact lenses and wear chemical safety goggles where contact with liquid or mist

may occur.

Skin Protection: Wear impervious gloves when contact with skin may occur. Use face shields where

splashing may occur. Wash with soap and water before eating, drinking or smoking.

Launder contaminated clothing before reuse. Discard contaminated shoes.

Inhalation: Use approved respiratory protective equipment for cleaning large spills or entry into

large tanks, vessels or other confined spaces or in situations where exposure may exceed occupational exposure levels. Avoid inhalation of vapors or mists generated by

heating or violent agitation of this product.

Ventilation: Provide adequate ventilation 1) to keep mist or vapors below occupational exposure levels

and 2) to prevent the formation of an oxygen deficient atmosphere, particularly in a confined

space area.

SPILL OR LEAK AND DISPOSAL PROCEDURES

Spill Procedures: Remove sources of heat or ignition including internal combustion engines and power

tools. Remove spill with vacuum trucks or pump and soak up residue with and absorbent.

Use approved respirator where occupational exposure limits may be exceeded.

Waste Disposal: Dispose through a licensed waste disposal company. Follow federal, state and local regulation.

SPECIAL PRECAUTIONS AND COMMENTS

Storage Requirements: Store in tightly closed containers in an dry cool place, away from incompatible materials or

sources of heat, ignition or strong oxidizers. Ground and bond all transfer and storage equipment. Empty containers may contain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, puncture, incinerate, weld, braze, solder, drill, grind or expose such

containers to heat, flame, sparks or other sources of ignition.

SARA TITLE III INFORMATION

Acute	Chronic	<u>Fire</u>	<u>Pressure</u>	Reactive
X	X			

SARA Hazardous Substances

<u>Ingredient</u>	CAS NO.	<u>%, WT</u>	Sec 313	Sec 302	RQ, lb	TPQ, lb
Ethylene glycol	110-80-5	N.A.	X			
Glycol Ethers	Various	>75	X			

Key: Sec 313 = **Toxic Chemicals, Section 313**

Sec 302 = Extremely Hazardous Substances (EHS)

RQ = Reportable Quantity of EHS

TPQ = Threshold Planning Quantity of EHS

CALIFORNIA PROPOSITION 65 WARNING

Chemicals known to the State of California to cause cancer, birth defects or other reproductive harm may be found in the petroleum products. Although it is possible to sufficiently refine the petroleum products to remove the potential for cancer, we are advising that one or more of the listed chemicals may be present in some detectable quantities. Read and follow directions and use care when handling these petroleum products.

THIS INFORMATION RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS TO THE BEST OF THIS COMPANY'S KNOWLEDGE AND BELIEVED ACCURATE AND RELIABLE AS OF THE DATE INDICATED. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MAKE AS TO THE ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABLENESS AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE.