

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 26.06.2014

Revision: 26.06.2014

## 1 Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Bead Sealer
- **Article number:** 14-101, 14-104, 14-101A, 14-101B, 14-104A, 14-104B
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Sealant
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**  
31 Incorporated  
100 Enterprise Dr.  
Newcomerstown, OH 43832  
Phone: (740) 498-8324
- **1.4 Emergency telephone number:**  
ChemTel Inc.  
(800)255-3924, +1 (813)248-0585

## 2 Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**  
The following Hazard Statements are applicable only to the general GHS regulations and not the specific CLP regulation: H361.  
The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H361d, H400, H410.



Repr. 2 H361: Suspected of damaging fertility or the unborn child.



flame

Flam. Liq. 2      H225      Highly flammable liquid and vapour.



health hazard

Repr. 2              H361d      Suspected of damaging the unborn child.  
STOT RE 2        H373      May cause damage to the central nervous system through prolonged or  
repeated exposure. Route of exposure: Inhalative.



environment

Aquatic Acute 1    H400      Very toxic to aquatic life.  
Aquatic Chronic 1 H410      Very toxic to aquatic life with long lasting effects.

(Contd. on page 2)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 26.06.2014

Revision: 26.06.2014

Trade name: **Bead Sealer**

(Contd. of page 1)



Skin Irrit. 2      H315    Causes skin irritation.  
 Skin Sens. 1      H317    May cause an allergic skin reaction.  
 STOT SE 3        H336    May cause drowsiness or dizziness.

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

Xn; Harmful

R48/20-63:      Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
 Possible risk of harm to the unborn child.

Xi; Irritant

R38:              Irritating to skin.

Xi; Sensitising

R43:              May cause sensitisation by skin contact.

F; Highly flammable

R11:              Highly flammable.

N; Dangerous for the environment

R50/53:         Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67:              Vapours may cause drowsiness and dizziness.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H410.

The product is classified and labelled according to the CLP regulation.

(Contd. on page 3)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 26.06.2014

Revision: 26.06.2014

Trade name: **Bead Sealer**

(Contd. of page 2)

- **Hazard pictograms**



This pictogram only applicable for EU regulations. Not for use in the United States (OSHA GHS).



GHS02 GHS07 GHS08 GHS09

- **Signal word** Danger

- **Hazard-determining components of labelling:**

toluene

Natural rubber latex

heptane

- **Hazard statements**

The following Hazard Statements are applicable only to the general GHS regulations and not the specific CLP regulation: H361.

H361: Suspected of damaging fertility or the unborn child.

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H361d, H410.

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H361d Suspected of damaging the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the central nervous system through prolonged or repeated exposure. Route of exposure: Inhalative.

H410 Very toxic to aquatic life with long lasting effects.

- **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P281 Use personal protective equipment as required.

P233 Keep container tightly closed.

P264 Wash thoroughly after handling.

P260 Do not breathe mist/vapours/spray.

P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.

P314 Get medical advice/attention if you feel unwell.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Hazard description:**

- **WHMIS-symbols:**

B2 - Flammable liquid

D2A - Very toxic material causing other toxic effects



(Contd. on page 4)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 26.06.2014

Revision: 26.06.2014

Trade name: **Bead Sealer**

(Contd. of page 3)

· **NFPA ratings (scale 0 - 4)**· **HMIS-ratings (scale 0 - 4)**

\* - Indicates a long term health hazard from repeated or prolonged exposures.

· **HMIS Long Term Health Hazard Substances**

108-88-3 | toluene

· **2.3 Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

## 3 Composition/information on ingredients

· **3.2 Mixtures**· **Description:** Mixture of substances listed below with nonhazardous additions.· **Dangerous components:**

CAS: 108-88-3 EINECS: 203-625-9 Index number: 601-021-00-3	toluene Xn R48/20-63-65;  Xi R38;  F R11 R67 Repr. Cat. 3 ----- Flam. Liq. 2, H225 Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304 Skin Irrit. 2, H315; STOT SE 3, H336	50-100%
CAS: 142-82-5 EINECS: 205-563-8 Index number: 601-008-00-2	heptane Xn R65;  Xi R38;  F R11;  N R50/53 R67 ----- Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Irrit. 2, H315; STOT SE 3, H336	25-50%
CAS: 9006-04-6	Natural rubber latex Xi R43 ----- Skin Sens. 1B, H317	<10%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

(Contd. on page 5)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 26.06.2014

Revision: 26.06.2014

**Trade name: Bead Sealer**

(Contd. of page 4)

## 4 First aid measures

### · 4.1 Description of first aid measures

#### · **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

#### · **After inhalation:**

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of irregular breathing or respiratory arrest provide artificial respiration.

In case of unconsciousness place patient stably in side position for transportation.

#### · **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation is experienced, consult a doctor.

#### · **After eye contact:**

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

#### · **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

A person vomiting while laying on their back should be turned onto their side.

### · 4.2 Most important symptoms and effects, both acute and delayed

Headache

Dizziness

Coughing

Cramp

Nausea

Allergic reactions

Gastric or intestinal disorders when ingested.

Disorientation

#### · **Hazards**

Danger of convulsion.

Danger of impaired breathing.

Danger of disturbed cardiac rhythm.

Condition may deteriorate with alcohol consumption.

May be harmful in contact with skin.

May be harmful if inhaled.

Repeated exposure may cause skin dryness or cracking.

### · 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

If necessary oxygen respiration treatment.

(Contd. on page 6)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 26.06.2014

Revision: 26.06.2014

Trade name: **Bead Sealer**

(Contd. of page 5)

## 5 Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
  - Foam
  - Alcohol resistant foam
  - Fire-extinguishing powder
  - Carbon dioxide
  - Gaseous extinguishing agents
  - Water haze or fog
  - CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water
- **5.2 Special hazards arising from the substance or mixture**
  - Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:**
  - Wear self-contained respiratory protective device.
  - Wear fully protective suit.
- **Additional information** Eliminate all ignition sources if safe to do so.

## 6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
  - Use respiratory protective device against the effects of fumes/dust/aerosol.
  - Wear protective equipment. Keep unprotected persons away.
  - Ensure adequate ventilation
  - Keep away from ignition sources.
  - Protect from heat.
- **6.2 Environmental precautions:**
  - Do not allow to enter sewers/ surface or ground water.
  - Inform respective authorities in case of seepage into water course or sewage system.
- **6.3 Methods and material for containment and cleaning up:**
  - Allow to solidify. Pick up mechanically.
  - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
  - Pick up mechanically.
  - Send for recovery or disposal in suitable receptacles.
  - Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
  - See Section 7 for information on safe handling.
  - See Section 8 for information on personal protection equipment.
  - See Section 13 for disposal information.

## 7 Handling and storage

- **7.1 Precautions for safe handling** Use only in well ventilated areas.

(Contd. on page 7)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 26.06.2014

Revision: 26.06.2014

Trade name: **Bead Sealer**

(Contd. of page 6)

- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Flammable gas-air mixtures may form in empty receptacles.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Provide ventilation for receptacles.  
Avoid storage near extreme heat, ignition sources or open flame.
- **Information about storage in one common storage facility:**  
Store away from foodstuffs.  
Store away from oxidizing agents.
- **Further information about storage conditions:**  
Store in cool, dry conditions in well sealed receptacles.  
Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

### · **Ingredients with limit values that require monitoring at the workplace:**

#### **108-88-3 toluene**

PEL (USA)	Short-term value: C 300; 500* ppm Long-term value: 200 ppm *10-min peak per 8-hr shift
REL (USA)	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm Long-term value: 375 mg/m <sup>3</sup> , 100 ppm
TLV (USA)	Long-term value: 75 mg/m <sup>3</sup> , 20 ppm BEI
EL (Canada)	Long-term value: 20 ppm R
EV (Canada)	Long-term value: 20 ppm

#### **142-82-5 heptane**

IOELV (EU)	Long-term value: 2085 mg/m <sup>3</sup> , 500 ppm
PEL (USA)	Long-term value: 2000 mg/m <sup>3</sup> , 500 ppm
REL (USA)	Short-term value: C 1800* mg/m <sup>3</sup> , C 440* ppm Long-term value: 350 mg/m <sup>3</sup> , 85 ppm *15-min
TLV (USA)	Short-term value: 2050 mg/m <sup>3</sup> , 500 ppm Long-term value: 1640 mg/m <sup>3</sup> , 400 ppm

(Contd. on page 8)

## Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 26.06.2014

Revision: 26.06.2014

**Trade name: Bead Sealer**

(Contd. of page 7)

EL (Canada)	Short-term value: 500 ppm Long-term value: 400 ppm
EV (Canada)	Short-term value: 2,045 mg/m <sup>3</sup> , 500 ppm Long-term value: 1,635 mg/m <sup>3</sup> , 400 ppm

**9006-04-6 Natural rubber latex**

TLV (USA)	Long-term value: 0,0001* mg/m <sup>3</sup> Skin; (SEN) NIC-DSEN, RSEN;* inh. fraction
EL (Canada)	Long-term value: 0,001 mg/m <sup>3</sup> inhalable, Skin; S
EV (Canada)	Long-term value: 0,001 mg/m <sup>3</sup> as total proteins, inhalable, Skin

- **DNELs** No further relevant information available.
- **PNECs** No further relevant information available.

**Ingredients with biological limit values:**
**108-88-3 toluene**

BEI (USA)	0,02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0,03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0,3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

- **Additional information:** The lists valid during the making were used as basis.

**8.2 Exposure controls**
**Personal protective equipment:**
**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.  
Pregnant women should strictly avoid inhalation or skin contact.  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.

**Respiratory protection:**

Not required under normal conditions of use.  
For spills, respiratory protection may be advisable.  
Use suitable respiratory protective device when high concentrations are present.  
Use suitable respiratory protective device when aerosol or mist is formed.  
NIOSH or EN approved organic vapor respirator equipped with a dust/mist prefilter should be used.

(Contd. on page 9)



# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 26.06.2014

Revision: 26.06.2014

Trade name: **Bead Sealer**

(Contd. of page 8)

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Safety glasses

- **Body protection:** Protective work clothing

- **Limitation and supervision of exposure into the environment**

No further relevant information available.

- **Risk management measures**

See Section 7 for additional information.

No further relevant information available.

## 9 Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

**Form:** Liquid

**Colour:** Black

- **Odour:** Solvent-like

- **Odour threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

**Melting point/Melting range:** Not Determined.

**Boiling point/Boiling range:** 210 ° F / 99 ° C

- **Flash point:** 16 ° F / -9 ° C (TCC D56)

- **Flammability (solid, gaseous):** Not applicable.

(Contd. on page 10)

## Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 26.06.2014

Revision: 26.06.2014

Trade name: **Bead Sealer**

(Contd. of page 9)

- **Auto/Self-ignition temperature:** 419 ° F/215 °C
- **Decomposition temperature:** Not determined.
- **Self-igniting:** Product is not self-igniting.
- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- **Explosion limits:**
  - Lower:** 1,1 Vol %
  - Upper:** 7,0 Vol %
- **Vapour pressure at 20 °C:** 48 hPa
- **Density at 20 °C:** 0,87 g/cm<sup>3</sup>
- **Relative density:** Not determined.
- **Vapour density:** Not determined.
- **Evaporation rate:** Not determined.
- **Solubility in / Miscibility with water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
  - Dynamic:** Not determined.
  - Kinematic at 20 °C:** 721 mm<sup>2</sup>/s (Converted from 5 Zahn)
- **Solvent content:**
  - VOC (California)** 75-90 % Wt
- **9.2 Other information:** No further relevant information available.

### 10 Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**  
Used empty containers may contain product gases which form explosive mixtures with air.  
Flammable.  
Reacts violently with oxidizing agents.  
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.  
Toxic fumes may be released if heated above the decomposition point.
- **10.4 Conditions to avoid**  
Keep ignition sources away - Do not smoke.  
Store away from oxidizing agents.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**  
Carbon dioxide

(Contd. on page 11)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 26.06.2014

Revision: 26.06.2014

Trade name: **Bead Sealer**

Carbon monoxide

(Contd. of page 10)

## 11 Toxicological information

### · 11.1 Information on toxicological effects

#### · Acute toxicity:

#### · LD/LC50 values relevant for classification:

##### 108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

##### 142-82-5 heptane

Oral	LD50	> 5000 mg/kg (rat) (Estimate)
Inhalative	LC50/4 h	103 mg/l (rat)

##### 1333-86-4 Carbon black

Oral	LD50	10000 mg/kg (rat)
------	------	-------------------

#### · Primary irritant effect:

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** Slight irritant effect on eyes.

· **Sensitization:** Sensitization possible through skin contact.

#### · Additional toxicological information:

Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

Toxic and/or corrosive effects may be delayed up to 24 hours.

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

Danger through skin adsorption.

#### · Repeated dose toxicity:

May cause damage to organs through prolonged or repeated exposure.

Repeated exposures may result in skin and/or respiratory sensitivity.

#### · CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):

Repr. 2

## 12 Ecological information

### · 12.1 Toxicity

· **Aquatic toxicity:** Toxic for aquatic organisms

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 12)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 26.06.2014

Revision: 26.06.2014

Trade name: **Bead Sealer**

(Contd. of page 11)

- **Additional ecological information:**
- **General notes:**  
Avoid transfer into the environment.  
Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Very toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Contact waste processors for recycling information.  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.  
Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.  
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

- **14.1 UN-Number**
- **DOT, ADR, IMDG, IATA** UN1133
- **14.2 UN proper shipping name**
- **DOT** Adhesives
- **ADR** 1133 ADHESIVES, ENVIRONMENTALLY HAZARDOUS
- **IMDG** ADHESIVES (HEPTANES), MARINE POLLUTANT
- **IATA** ADHESIVES
- **14.3 Transport hazard class(es)**
- **DOT**
- **Class** 3 Flammable liquids.



(Contd. on page 13)

## Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 26.06.2014

Revision: 26.06.2014

Trade name: **Bead Sealer**

(Contd. of page 12)

· **Label**

3

· **ADR**· **Class**

3 (F1) Flammable liquids.

· **Label**

3

· **IMDG**· **Class**

3 Flammable liquids.

· **Label**

3

· **IATA**· **Class**

3 Flammable liquids.

· **Label**

3

· **14.4 Packing group**· **DOT, ADR, IMDG, IATA**

III

· **14.5 Environmental hazards:**

Product contains environmentally hazardous substances: heptane

· **Marine pollutant:**

Yes

· **Special marking (ADR):**

Symbol (fish and tree)

· **14.6 Special precautions for user**

Symbol (fish and tree)

· **Danger code (Kemler):**

Warning: Flammable liquids.

· **EMS Number:**

33

· **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**F-E,S-E

Not applicable.

· **Transport/Additional information:**· **ADR**· **Limited quantities (LQ)**

5L

· **Transport category**

3

· **Tunnel restriction code**

D/E

· **UN "Model Regulation":**

UN1133, ADHESIVES, ENVIRONMENTALLY HAZARDOUS, 3, III

(Contd. on page 14)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 26.06.2014

Revision: 26.06.2014

Trade name: **Bead Sealer**

(Contd. of page 13)

## 15 Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

108-88-3 | toluene

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

- **Proposition 65 (California):**

- **Chemicals known to cause cancer:**

References to chemical components listed below are based on unbound respirable particles and are not generally applicable to product as supplied.

1333-86-4 | Carbon black

- **Chemicals known to cause reproductive toxicity for females:**

108-88-3 | toluene

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

108-88-3 | toluene

- **Carcinogenic Categories**

- **EPA (Environmental Protection Agency)**

108-88-3 | toluene

II

142-82-5 | heptane

D

- **IARC (International Agency for Research on Cancer)**

108-88-3 | toluene

3

1333-86-4 | Carbon black

2B

- **TLV (Threshold Limit Value established by ACGIH)**

108-88-3 | toluene

A4

1333-86-4 | Carbon black

A4

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4 | Carbon black

- **Canada**

- **Canadian Domestic Substances List (DSL)**

All ingredients are listed.

- **Canadian Ingredient Disclosure list (limit 0.1%)**

None of the ingredients is listed.

(Contd. on page 15)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 26.06.2014

Revision: 26.06.2014

Trade name: **Bead Sealer**

(Contd. of page 14)

<b>· Canadian Ingredient Disclosure list (limit 1%)</b>	
108-88-3	toluene
142-82-5	heptane

<b>· Other regulations, limitations and prohibitive regulations</b>
<b>· Substances of very high concern (SVHC) according to REACH, Article 57</b>
None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H373 May cause damage to the central nervous system through prolonged or repeated exposure. Route of exposure: Inhalative.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

R11 Highly flammable.

R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R63 Possible risk of harm to the unborn child.

R65 Harmful: may cause lung damage if swallowed.

R67 Vapours may cause drowsiness and dizziness.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

(Contd. on page 16)

**Safety Data Sheet**  
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 26.06.2014

Revision: 26.06.2014

**Trade name: Bead Sealer**

(Contd. of page 15)

LD50: Lethal dose, 50 percent  
Flam. Liq. 2: Flammable liquids, Hazard Category 2  
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2  
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1  
Skin Sens. 1B: Sensitisation - Skin, Hazard Category 1B  
Repr. 2: Reproductive toxicity, Hazard Category 2  
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3  
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2  
Asp. Tox. 1: Aspiration hazard, Hazard Category 1  
Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1  
Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

**Sources**

SDS Prepared by:  
ChemTel Inc.  
1305 North Florida Avenue  
Tampa, Florida USA 33602-2902  
Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573  
Website: [www.chemtelinc.com](http://www.chemtelinc.com)