



MATERIAL SAFETY DATA SHEET

Section 1: Product & Company Identification

Product Name: Hi Temperature Disc Brake Wheel Bearing Grease

Product Number (s): SL3160, SL3161, SL3165, SL3166

Product Use: Wheel Bearing Grease

Manufacturer / Supplier Contact Information:

In United States:

CRC Industries, Inc.
885 Louis Drive
Warminster, PA 18974
www.crcindustries.com
1-215-674-4300 (General)
(800) 521-3168 (Technical)
(800) 272-4620 (Customer Service)

In Canada:

CRC Canada Co.
2-1246 Lorimar Drive
Mississauga, Ontario L5S 1R2
www.crc-canada.ca
1-905-670-2291

In Mexico:

CRC Industries Mexico
Av. Benito Juárez 4055 G
Colonia Orquídea
San Luís Potosí, SLP CP 78394
www.crc-mexico.com
52-444-824-1666

24-Hr Emergency – CHEMTREC: (800) 424-9300 or (703) 527-3887

Section 2: Hazards Identification

Emergency Overview

Appearance & Odor: Black semi-solid to solid grease with a faint petroleum odor

Potential Health Effects:

ACUTE EFFECTS:

EYE: May cause mild irritation.

SKIN: Repeated or prolonged contact can result in drying of the skin.

INHALATION: Heating can generate vapors that may cause respiratory irritation, nausea and headaches. Inhalation hazard at room temperature is unlikely due to the low volatility of this product.

INGESTION: Can cause stomach ache and vomiting. Main hazard, if ingested, is aspiration into the lungs and subsequent pneumonitis.

CHRONIC EFFECTS: Unknown

TARGET ORGANS: None known

Medical Conditions Aggravated by Exposure: Skin or respiratory conditions

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Product Name: Hi Temperature Disc Brake Wheel Bearing Grease

Product Number (s): SL3160, SL3161, SL3165, SL3166

Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.
Hydrotreated heavy naphthenic distillates	64742-52-5	50 – 70
Petroleum oils, solvent-dewaxed	64742-62-7 / 64742-65-0	10 - 30
Aluminum complex thickener	proprietary	5 – 10
Antimony dialkyldithiocarbamate	Proprietary	1 - 2
Graphite	7782-42-5	0.5 – 1.5
Naphthalenesulfonic acid, dinonyl-	57855-77-3	0.5 – 1.5

Section 4: First Aid Measures

Eye Contact: Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

Skin Contact: Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.

Inhalation: Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.

Ingestion: DO NOT induce vomiting. Seek medical attention.

Note to Physicians: Treat symptomatically

Section 5: Fire-Fighting Measures

Flammable Properties: As defined by OSHA, this product is non-flammable.

Flash Point: > 450°F / 232°C (COC) Upper Explosive Limit: ND
Autoignition Temperature: ND Lower Explosive Limit: ND

Fire and Explosion Data:

Suitable Extinguishing Media: CO², dry chemical, sand, dolomite, alcohol resistant foam, water spray

Products of Combustion: Oxides of carbon. Sulfur. Acrid smoke/fumes.

Explosion Hazards: Containers, when exposed to heat from fire, may build pressure and rupture.

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition. Avoid water in straight hose stream as it will scatter and spread fire.

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8. Minimize skin contact.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains. Advise authorities if product has entered waterways.

Product Name: Hi Temperature Disc Brake Wheel Bearing Grease

Product Number (s): SL3160, SL3161, SL3165, SL3166

Methods for Containment & Clean-up: Dike area to contain spill. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

Section 7: Handling and Storage

Handling Procedures: Keep container away from heat, sparks, and open flame. High temperatures may produce irritating vapors. Eye wash station should be available at work place. Keep containers closed when not in use. Ventilate well, especially in warmer environments. For product use instructions, please see the product label.

Storage Procedures: Store in a cool dry area out of direct sunlight. Store separated from acids and oxidizing materials. Store away from sparks and open flame.

Aerosol Storage Level: NA

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

COMPONENT	OSHA		ACGIH		OTHER		UNIT
	TWA	STEL	TWA	STEL	TWA	SOURCE	
Hydrotreated heavy naphthenic distillate	5*	NE	5*	10*	NE		mg/m ³
Petroleum oils, solvent-dewaxed	5*	NE	5*	10*	NE		mg/m ³
Aluminum complex thickener	NE	NE	NE	NE	NE		
Antimony dialkyldithiocarbamate	0.5	NE	0.5	NE	NE		mg/m ³
Graphite	15**	NE	2	NE	2.5	NIOSH	mg/m ³
Naphthalenesulfonic acid, dinonyl-	NE	NE	NE	NE	NE		
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated * – oil mist ** - mppcf							

Controls and Protection:

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic cartridge. Air monitoring is needed to determine actual employee exposure levels. Use a self-contained breathing apparatus in confined spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as neoprene, nitrile, polyethylene or PVC. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

Product Name: Hi Temperature Disc Brake Wheel Bearing Grease

Product Number (s): SL3160, SL3161, SL3165, SL3166

Section 9: Physical and Chemical Properties

Physical State: semi-solid grease

Color: black

Odor: mild petroleum

Odor Threshold: ND

Specific Gravity: 0.90 @ 60°F / 16°C

Initial Boiling Point: ND

Freezing Point: ND

Vapor Pressure: < 0.01 mmHg @ 68°F / 20°C

Vapor Density: > 5 (air = 1)

Evaporation Rate: slow

Solubility: insoluble in water

Coefficient of water/oil distribution: ND

pH: NA

Volatile Organic Compounds: wt %: 0.4 g/L: 3.6 lbs./gal: 0.03

Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid: None

Incompatible Materials: Avoid contact with acids and oxidizing agents.

Hazardous Decomposition Products: Oxides of carbon, sulfur

Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

Acute Toxicity:

<u>Component</u>	<u>Oral LD50 (rat)</u>	<u>Dermal LD50 (rabbit)</u>	<u>Inhalation LC50 (rat)</u>
Hydrotreated heavy naphthenic distillate	> 5000 mg/kg	> 2000 mg/kg	2.18 mg/L/4H
Petroleum oils, solvent-dewaxed	> 2000 mg/kg	> 2000 mg/kg	> 5 mg/L/4H
Aluminum complex thickener	No data	No data	No data
Antimony dialkyldithiocarbamate	No data	No data	No data
Graphite	No data	No data	No data
Naphthalenesulfonic acid, dinonyl-	> 5000 mg/kg	> 2000 mg/kg	> 18,000 mg/m ³ /1H

Chronic Toxicity:

<u>Component</u>	<u>OSHA Carcinogen</u>	<u>IARC Carcinogen</u>	<u>NTP Carcinogen</u>	<u>Irritant</u>	<u>Sensitizer</u>
Hydrotreated heavy naphthenic distillate	No	No	No	No	Unknown
Petroleum oils, solvent-dewaxed	No	No	No	No	No
Aluminum complex thickener	No	No	No	No	Unknown
Antimony dialkyldithiocarbamate	No	No	No	Unknown	Unknown
Graphite	No	No	No	Unknown	Unknown
Naphthalenesulfonic acid, dinonyl-	No	No	No	skin	Unknown

Product Name: Hi Temperature Disc Brake Wheel Bearing Grease

Product Number (s): SL3160, SL3161, SL3165, SL3166

Reproductive Toxicity: No information available
Teratogenicity: No information available
Mutagenicity: No information available
Synergistic Effects: No information available

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity: Naphthenic distillates: 48 Hr EC50 Daphnia magna: >1000 mg/L
Persistence / Degradability: No information available
Bioaccumulation / Accumulation: No information available
Mobility in Environment: No information available

Section 13: Disposal Considerations

Waste Classification: This product is not a RCRA hazardous waste. (See 40 CFR Part 261.20 – 261.33)
Empty containers may be recycled.

All disposal activities must comply with federal, state, provincial and local regulations. Local regulations may be more stringent than state, provincial or national requirements.

Section 14: Transport Information

US DOT (ground): Not Regulated
ICAO/IATA (air): Not Regulated
IMO/IMDG (water): Not Regulated
Special Provisions: None

Section 15: Regulatory Information

U.S. Federal Regulations:

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: None

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories: Fire Hazard No
 Reactive Hazard No

Product Name: Hi Temperature Disc Brake Wheel Bearing Grease

Product Number (s): SL3160, SL3161, SL3165, SL3166

Release of Pressure	No
Acute Health Hazard	No
Chronic Health Hazard	No

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:
Antimony compounds (< 2%)

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): None

Occupational Safety and Health Administration:

This product is regulated by the Hazard Communications Standard.

U.S. State Regulations:

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm: None

Consumer Products VOC Regulations: This product is not regulated.

State Right to Know:

New Jersey: NJTSRN 800983-5015P
Pennsylvania: 15890-25-2, 7782-42-5
Massachusetts: 7782-42-5
Rhode Island : 7782-42-5

Canadian Regulations:

Controlled Products Regulations:

This product has been classified in accordance with the hazard criteria of the Controlled Product Regulation and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Hazard Class: This product is not regulated.

Canadian DSL Inventory: All ingredients are either listed on the DSL Inventory or are exempt.

European Union Regulations:

RoHS Compliance: This product is compliant with Directive 2002/95/EC of the European Parliament and of the Council of 27 January 2003. This product does not contain any of the restricted substances as listed in Article 4(1) of the RoHS Directive.


Additional Regulatory Information: None

Product Name: Hi Temperature Disc Brake Wheel Bearing Grease

Product Number (s): SL3160, SL3161, SL3165, SL3166

Section 16: Other Information

HMIS® (II)	
Health:	1
Flammability:	1
Reactivity:	0
PPE:	B



Ratings range from 0 (no hazard) to 4 (severe hazard)

Prepared By: Michelle Rudnick

CRC #: 2929SL

Revision Date: 02/18/2013

Changes since last revision: MSDS reformatted to meet the requirements of the Canadian Controlled Products Regulations.

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this MSDS consult your supervisor, a health & safety professional, or CRC Industries.

ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstract Service

CFR: Code of Federal Regulations

DOT: Department of Transportation

DSL: Domestic Substance List

g/L: grams per Liter

HMIS: Hazardous Materials Identification System

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

IMDG: International Maritime Dangerous Goods

IMO: International Maritime Organization

lbs./gal: pounds per gallon

LC: Lethal Concentration

LD: Lethal Dose

NA: Not Applicable

ND: Not Determined

NIOSH: National Institute of Occupational Safety & Health

NFPA: National Fire Protection Association

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PMCC: Pensky-Martens Closed Cup

PPE: Personal Protection Equipment

ppm: Parts per Million

RoHS: Restriction of Hazardous Substances

STEL: Short Term Exposure Limit

TCC: Tag Closed Cup

TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Information System